



Technical conditions of work execution (TCWE): pickling carbon steel – at the pickling plant of FK system – povrchové úpravy, s.r.o.

These TCWE do not replace the General Terms and Conditions of FK system – povrchové úpravy, s.r.o.

1. Acceptance of a part for surface treatment

- 1.1. An order to be emailed at least 1 day in advance to fksystem@fksystem.cz, which is the only address to receive and process orders. Orders are confirmed only electronically by a confirmation sent from the system. Without an order, goods will not be released for treatment.
Among other things, an order must state:
 - customer identification
 - ref. No. of our offer, if any has been made
 - identification of the part(s) or order
 - required surface treatment
 - quality of material (if there are more types, all of them)
 - any special requirements for packaging, handling, etc.
- 1.2. Parts must be delivered with a delivery note referring to the order number under which treatment was ordered.
- 1.3. If the parts are machined or there is a risk of confusion with stainless steel material, it is necessary to indicate the material designation prominently in the order so that no confusion can occur and at the same time inform the technician of the pickling plant or the master of the pickling plant by phone.
- 1.4. Parts to be pickled must be delivered dry, without grease, without any paint or marker markings, etc. and without mechanical impurities, incl. stickers, burnt foils, etc. Delivery of parts failing to meet this requirement may result in poorer visual quality of the pickled surface.
- 1.5. After prior agreement with the technician, parts can be delivered, e.g. greasy for degreasing, with scales after annealing for removing scale, with protective foil, if necessary, etc.
- 1.6. Only a random check is performed on receipt. Any damage can only be detected after work on the parts has started. The number of pieces is not checked. On request, it is possible to order 100% acceptance of parts.

2. Quality standards:

- 2.1. Pickling and passivation are technical operations ensuring corrosion resistance of the material. They cannot achieve a uniform or repeatable surface appearance.
- 2.2. The surface after pickling and passivation will be clean without gross corrosion. The passivation solution may cause a brownish appearance to the surface.
- 2.3. Pickling cannot remove slag, burnt grease, paint, dirt ground or pressed into the surface, strong scale, markings, etc.
- 2.4. The passive layer protects the carbon steel surface against corrosion in days to weeks depending on the storage method. Passivated parts must be stored appropriately and used and put into operation as soon as possible or otherwise protected.
- 2.5. Defects cannot be claimed on poorly accessible or completely inaccessible surfaces.
- 2.6. On request, we provide a report on the work performed according to the technical standard ČSN EN 10204 – 2.1. We issue an inspection certificate according to ČSN EN 10204 – 3.1 for an additional fee after the customer defines required tests.

3. Problem areas in terms of pickling

- 3.1. Dip-pickled parts must not have closed spaces (square tubes, pipes, etc.) that are not watertight and into which pickling agents could seep without the possibility of rinsing.
- 3.2. If there are joints (stitch welds, sheet metal on sheet metal, screw joints, etc.), porosity (e.g. in castings), or other surface inhomogeneity, residues of pickling agent or rinsing water may remain in the parts. These may subsequently flow out or ooze out and form rusty maps on the



surface. Any defects arising due to construction details mentioned in points 3.1 and 3.2 or others, non-compliance with delivery conditions 1.4 or others are not considered to be pickling defects and we do not recognize them as a claim.

4. Packaging

- 4.1. After pickling, parts are shipped packaged in the same way they were delivered. In the event of a request for a different packaging method, this must be agreed with the technician and included in the order. Packaging other than the basic type (section 4.3) is subject to a charge.
- 4.2. The basic method of packaging is included in the price of the work.
- 4.3. Basic packaging includes clean packaging material as a base on a pallet, in a box, etc. It also includes placing the parts on a pallet or in a box, strapping them to the pallet and possibly covering the entire pallet or box with clean PE foil.
- 4.4. EXTRA packaging can be ordered for an additional fee. EXTRA packaging means that each part is packed separately, or individual layers of parts are horizontally separated from each other by cardboard, and also the parts in each layer are separated from each other by cardboard or foil.
- 4.5. Packaging is not intended for open trucks and is not intended for storage in outdoor, unsheltered places.

5. Shipment of parts after surface treatment

- 5.1. If parts are picked up by an external carrier, it is necessary for the driver to report the name of the company that ordered the surface treatment and the order number for which the treatment was ordered. Without this, it is not possible to identify the order and carry out the loading.
- 5.2. Our company does not arrange transport nor does it assume any responsibility for proper and careful securing of goods for the purpose of transport on a vehicle. The driver/carrier assumes responsibility for the subject of the order on loading the goods and signing the delivery note.